

JS1602

Blehschere 1,6mm



Pos.	Artikel-Nr.	PG	Bezeichnung	Stk.	Pos.	Artikel-Nr.	PG	Bezeichnung	Stk.
1	266053-1	3	BLECHSCHRAUBE 4x35	4	62	453884-9	16	MOTORGEHAEUSEABDECKUNG	1
2	141691-9	34	GETRIEBEGEHAEUSE	1					
2,1	800H33-1	99	HINWEISSCHILD	1					
3	210030-5	8	RILLENKUGELLAGER 627ZZ	1				*** ZUBEHÖR ***	
4	253823-7	2	SCHEIBE 7	1					
5	331151-1	25	PLEUELSTANGE	1	Z	191383-0	37	MESSERSATZ INKL. 17	1
6	212063-6	18	NADELLAGER 1012	1	Z	410048-8	2	SCHLUESSELHALTER 3,4	1
7	253758-2	2	SCHEIBE 10	1	Z	783201-2	2	SECHSKANTSTIFTSCHLUESSEL 3mm	1
8	141690-1	34	KURBELWELLE	1					
8,1	227760-1	99	STIRNRAD 44	1					
9	210033-9	17	RILLENKUGELLAGER 696ZZ	1					
10	442185-0	3	DICHTUNG	1					
11	454076-3	23	LAGERSCHILD	1					
12	256110-3	3	STIFT 6	1					
13	913427-4	4	MADENSCHRAUBE M8x16	1					
14	346620-9	21	SCHUTZBLECH	1					
15	922206-9	2	INNENSECHSKANTSCHRAUBE M5x10	1					
16	321311-3	31	HUBSTANGE	1					
17	253334-2	2	UNTERLAGSCHEIBE 5	1					
19	922112-8	1	INNENSECHSKANTSCHRAUBE M4x10	1					
21	311717-3	61	SCHNEIDTISCH	1					
22	922127-5	1	INNENSECHSKANTSCHRAUBE M4x16	1					
23	251986-3	1	INNENSECHSKANTSCHRAUBE M6x6	1					
37	210005-4	18	RILLENKUGELLAGER 608DDW	1					
39	517674-5	42	ANKER INKL. 37, 40, 41	1					
40	681636-0	3	ISOLIERSCHEIBE	1					
41	210062-2	8	RILLENKUGELLAGER 607ZZ	1					
42	421868-5	9	GUMMIHUELSE 19	1					
43	450796-7	4	FELDABDECKUNG	1					
44	452073-3	8	DISTANZSTUECK	1					
45	623549-9	35	FELD	1					
46	266004-4	8	SCHRAUBE M4x70	2					
47	265954-0	1	BLECHSCHRAUBE PT 3x8	2					
48	643839-4	11	KOHLEHALTER 6X9	2					
49	194722-3	13	KOHLEBUERSTEN CB-459	1					
50	450795-9	19	MOTORGEHAEUSE	1					
51	418016-5	1	SCHALTKNOPF	1					
52	450797-5	4	SCHALTHEBEL	1					
53	897764-3	99	TYPENSCHILD JS1602	1					
54	233121-5	1	DRUCKFEDER 4	1					
55	650621-4	15	SCHALTER PS-10	1					
56	687682-1	2	KABELKLEMMPLATTE	1					
57	265995-6	1	SCHRAUBE 4x18	1					
58	638739-1	6	KONDENSATOR	1					
59	682566-8	6	KNICKSCHUTZ	1					
60	665890-4	23	ANSCHLUSSLEITUNG H07RN-F	1					
61	265995-6	1	SCHRAUBE 4x18	1					

JS1602

Blehschere 1,6mm

